

# TECHNICAL SPECIFICATIONS

360° ROTATING DUPLEX OUTLET

2 POLE, 3 WIRE GROUNDING

15A 125V

## DUPLEX OUTLET FEATURES

- Exclusive "Plug and Turn" System with premium copper to copper contacts provide unlimited 360° rotation and continuous power even during rotation.
- One-step wallplate mounting without the need for secondary alignment plates.
- Top and bottom receptacles turn and hold in 18 unique positions for maximum flexibility.
- Premium copper blade and ground contacts provide consistent long term retention.
- Backwire clamps for secure termination of #12 - #14 AWG solid wire. Also, sidewire compatible for #12 - #14 AWG solid wire.
- Typical receptacle dimensions fit standard size electrical boxes.
- Includes decorative screwless wallplate for a designer finish.
- Patented non-metallic dielectric safety strap cannot become energized and safely covers wires and terminals.

CATALOG NUMBER	COLOR	RATING	NEMA
36010-W	White	15A 125V	5-15R
36011-V	Ivory	15A 125V	5-15R
36012-A	Almond	15A 125V	5-15R
36014-B	Black	15A 125V	5-15R

### MATERIALS OVERVIEW

FLAMMABILITY: UL94 V2

### TESTING STANDARDS & CODE COMPLIANCE

UL LISTED

UL 498 (FILE NO. E304553)

UL 514D (FILE NO. E312254)

NEMA WD-6



NEMA  
5-15R

renu

RENU™ SCREWLESS WALLPLATE AND WIDE SAFETY STRAP ARE LICENSED FROM CHEETAH USA CORP.

